

L' ACOUSTICS X15 HIQ

STAGE MONITOR

The X15 HiQ is the ultimate stage monitor: impressively powerful, yet melting into the stage with an ultra-sleek profile. Its active design and low-latency preset guarantee the best experience on stage.

Its 40° x 60° beam-width focuses on the artist only, offering an excellent acoustic isolation from other performers. Able to take on even the most energetic of artists, the X15 HiQ is built to take abuse yet remain strong and flexible - its built-in risers allowing it to be angled at 35° or 55° onstage.

At only 21 kgs / 46 lbs, the X15 HiQ is easy to rig or mount in any situation and will ensure minimum space and weight in trucks. A wide range of rigging accessories offers infinite install possibilities, including special narrow fill applications.



FEATURES | SPECIFICATIONS | BENEFITS

- Touchscreens: (4) Daylight visible 12.1"
- Usable bandwidth: (-10 dB): 55 Hz - 20 kHz ([X15] preset)
- Maximum SPL1: 138 dB ([X15] preset)
- Nominal directivity: Vertical: 60° Horizontal: 40°
- Monitoring angle: 35° without risers 55° with risers
- Transducers
LF: 1 × 15" neodymium, bass-reflex, laminar vents
HF: 1 × 3" neodymium compression driver, ellipsoid waveguide
- Nominal impedance: LF: 8 Ω | HF: 8 Ω
- Connectors: IN: SpeakON® | LINK: SpeakON®
- Rigging & handling: 2 × handles
DIN580-compatible M8 threaded insert
4 × M10 threaded inserts
2 × 35 mm pole sockets
- Dimensions: (W) 16.9in x (H) 22.8in x (D) 14.8in
- Weight (net): 46.2 lb
- IP: IP43



SHOW TECHNOLOGY